



2G / 3G Antene

MINISTUB ANTENNA | SMA



1011.03.JF MiniStub Antenna SMA
Antenna to be fitted directly on connector

- Frequency: AMPS 850 / DCS 1800 / UMTS 2100
- Impedance: 50 ohm
- Temperature: -40 +85°C
- Gain: < 2.2 dBi
- Dimensions: Ø 10 x 54 mm
- Connector: FME female
- Mounting: on SMA connector

MAGNETIC+ SMA



1011.02.JS Magnetic+ SMA Antenna
Magnetic antenna for metallic surfaces

- Frequency: AMPS 850 / GSM 900 / DCS 1800 / PCS 1900 / UMTS 2100
- Impedance: 50 ohm
- Temperature: -40 +85°C
- Gain: > 0 dBi
- Dimensions: Ø 31 x 72 mm
- Cable: 2.5 m RG174
- Connector: SMA male
- Mounting: Magnetic base

STRIP+ SMA



1011.01.JS Strip+ SMA Antenna
Adhesive antenna for non metallic surfaces

- Frequency: AMPS 850 / GSM 900 / DCS 1800 / PCS 1900 / UMTS 2100 / ISM 868 MHz
- Impedance: 50 ohm
- Temperature: -40 +85°C
- Gain: > 0 dBi
- Dimensions: 116 x 22 x 7 mm
- Cable: 2.5 m RG174
- Connector: SMA male
- Mounting: Adhesive strip

2G / 3G / 4G Antene

STUB4 ANTENNA | SMA



1011.40.00 STUB4 Antenna SMA
Antenna to be fitted directly on connector

- Frequency: 790-850 MHz / 1710-2105 MHz / 2380-2700 MHz
- Impedance: 50 ohm
- Temperature: -20 +60°C
- Gain: < 0 dBi
- Dimensions: Ø 10 x 50 mm
- Connector: SMA male
- Mounting: on SMA connector

MAGNETIC4 ANTENNA | SMA



1011.43.25 MAGNETIC4 Antenna SMA
Magnetic antenna for metallic surfaces

- Frequency: 700-960 MHz / 1710-2700 MHz
- Impedance: 50 ohm
- Temperature: -40 +80°C
- Gain: < 2.1 dBi
- Dimensions: Ø 29 x 100 mm
- Cable: 2.5 m RG174
- Connector: SMA male
- Mounting: Magnetic base

MINIFINGER ANTENNA | SMA



1011.04.JS MiniFinger Antenna SMA
Multiband outdoor antenna

- Frequency: 698-960 MHz / 1710-2170 MHz / 2500-2700 MHz
- Impedance: 50 ohm
- Temperature: -40 +85°C
- Gain: < 2 dBi
- Dimensions: Ø 16 x 210 mm
- Cable: 3.0 m LMR195
- Connector: SMA male
- Mounting: Wall / Pole

BODY4 ANTENNA | SMA



1011.42.20 BODY4 Antenna SMA
Body mount outdoor antenna

- Frequency: 824-960 MHz / 1710-2700 MHz
- Impedance: 50 ohm
- Temperature: -40 +85°C
- Gain: < 0 dBi
- Dimensions: Ø 94 x 18 mm
- Cable: 2.0 m RG174
- Connector: SMA male
- Mounting: 15mm hole + adhesive gasket



Zastopa in prodaja :

Legada d.o.o.

Ul.15.maja 2, SI-6000 Koper

Tel.: +386(0)5 90 54 402

www.legada.com , info@legada.com